## **AMENDMENTS TO THE SPECIFICATION**

Please replace Paragraph [0096] with the following paragraph rewritten in amendment format:

Referring now to Figure 22, a compressor 510' is shown. Compressor 510' is the same as compressor 510 except that solenoid valve 532 has been replaced by solenoid valve 532'. Solenoid valve 532' is located outside of shell 12 as opposed to solenoid valve 532 which is located within shell 12. A fluid pipe 542 extends through a fitting 544 attached to end cap 514 to place solenoid valve 532' in communication with annular chamber 580. A fluid pipe 546 extends between solenoid valve 532' and suction inlet fitting 522 or is otherwise connected to the suction chamber of compressor 510' to place solenoid valve 532' in communication with the suction pressure zone of compressor [[510]] 510'. The function and operation of compressor 510' and solenoid valve 532' are the same as described above for compressor 510 and solenoid valve 532.

**AMENDMENTS TO THE DRAWINGS** 

The attached "Replacement Sheets" of drawings include changes to Figures 1, 3,

5, 15 and 19. The attached "Replacement Sheets," which include Figures 1-24, replace

the original sheets including Figures 1-24.

Figure 1 – Please add reference numeral 150 and its associated leader line.

Figure 3 – Please add reference numeral 186 and its associated leader line.

Figure 5 – Please add reference numerals 178, 180 and 182 and their associated

leader lines.

Figure 15 – Please add cross-hatching to plug 326 and change reference

numeral 322 to 332.

Figure 19 – Please extend the bottom end of the leader line for reference

numeral 130.

Attachment: Replacement Sheets

Serial No. [10/619,767]